



Usage:	Entrance door for buildings
Opening:	Outside
Resistance to wind load:	NPD
Water tightness:	2A
Heat transmission value (U):	0,97 W=(m <sup>2</sup> *K)
Air permeability:	Class 4
Load-bearing capacity of safety devices:	NPD
Acoustic performance:	Rw 25 – 32 dB

## TECHNICAL SPECIFICATIONS

Sizes:	700–1200 x 1500-2400 mm Possible to produce as double-door
Door thickness:	62 mm
Frame:	42 x 105 mm pine frame
Clear opening (door open 90°)	M9-731mm, M10-831mm, M11-931mm
Insulation:	EPS 200 (55 mm)
Door skin:	On both sides: 3,2 mm HDF (Lesonit H10 high density fiberboard) + 0,3 mm thick aluminium sheet
Glazing:	2K 4-20 mm; 2K 6-16 mm LowE + Argon filling + warm spacer; Clear glass as standard, Satin, Crepi and Cotzwold as option
Glazing lists:	PVC; glazing bar 16 x 16 mm, crosslist RL 16 x 28 mm
Sealing:	in door leaf
Lock-case:	ASSA 2002
Stricking-plate:	VRR200/40, adjustable
Hinges:	N3248-110; height adjustable, burglary protected lift hinges; 4 pcs per door leaf
Threshold:	Aluminium + oak, 23 mm

